

# **BAND-IT<sup>®</sup>**



## **Industrial Insulation Banding Systems**

*For a safer and more efficient work environment*



**BAND-IT<sup>®</sup> offers industrial insulation customers increased efficiencies by providing value-added solutions at a competitive price**

- Save time, decrease labor costs and reduce waste with pre-cut and pre-assembled BAND-FAST<sup>®</sup> products
- Increase safety with no sharp edges
- Diminish snagging and injury with low profile BAND-IT Pro-Lokt<sup>™</sup> wing seals
- Resist cracking and breaking with UV resistant painted COLOR-IT<sup>®</sup> coatings
- Reduce labor time with the BAND-IT<sup>®</sup> Bantam Tool

**Features of BAND-IT<sup>®</sup> products used in the industrial insulation industry**

- BAND-FAST<sup>®</sup> and coils processed to eliminate camber
- Forms to any surface
- Banding products come in a broad size range and a wide selection of materials
- Painted COLOR-IT<sup>®</sup> coatings are available in a variety of colors

**[www.band-it-idex.com](http://www.band-it-idex.com)**

# Industrial Insulation Banding Systems



**BAND-FAST®**

## BAND-FAST®

BAND-FAST® is pre-cut band with pre-assembled patent-pending Pro-Lokt™ wing seals. It is the cut-to-order alternative to coils allowing distributors and contractors to focus on their core competencies of supplying and installing insulation. BAND-FAST® promotes a safe work environment with smoother edges and a more efficient working environment with decreased installation labor.

Part No	Material	Description
Call	304 SS	Call for a BAND-FAST configuration to meet your specific needs



**Ribbon Wound Coil**

## Coils

Oscillate wound coils (OWC) and ribbon wound coils (RWC) are available in a variety of colors with painted COLOR-IT® coatings. Blue coated 1/2" and 3/4" banding is stocked.

Part No	Material	Description
X30604	304 SS	Non-Coated RWC 1/2" X 0.38mm X 200m
X30606	304 SS	Non-Coated RWC 3/4" X 0.51mm X 200m
X31604	316 SS	Non-Coated RWC 1/2" X 0.38mm X 200m
X31606	316 SS	Non-Coated RWC 3/4" X 0.51mm X 200m
Call	304 SS	Non-Coated RWC
Call	304 SS	Non-Coated Oscillate Coil
Call	304 SS	COLOR-IT® Coated RWC
Call	304 SS	COLOR-IT® Coated Oscillate Coil



**Oscillate Coils with COLOR-IT®**

## Pro-Lokt™ and Wing Seals

Patent-pending Pro-Lokt™ was developed to meet customer for safety with rounded wings that eliminate sharp edges. They offer a lower profile to reduce snagging and injury while holding a retained force.

Part No	Material	Description	Package Quantity
AKWM-E08	304 SS	Pro-lokt® 1/2" Pro-Seal	1000/box
AKWM-E12	304 SS	Pro-lokt® 3/4" Wing Seal	1000/box
AKWM-F08	316 SS	Pro-lokt® 1/2" Clip	1000/box
AKWM-F12	316 SS	Pro-lokt® 3/4" Wing Seal	1000/box
AKWC-E08	304 SS	Pro-Lokt® 1/2" Wing Seal	100/box
AKWC-F08	316 SS	Pro-Lokt® 1/2" Wing Seal	100/box
AKWC-E12	304 SS	Pro-Lokt® 3/4" Wing Seal	100/box
AKWC-F12	316 SS	Pro-Lokt® 3/4" Wing Seal	100/box



**Pro-Lokt™**

## Bantam Tool

The Bantam Tool is designed for use in banding widths for light duty 3/16" to 3/4" banding applications. It further increases safety and convenience by incorporating a cutter and hammer within the tool.



**Bantam Tool**

Part No	Description	Package Quantity
C07569	Bantam Tool low torque - For band widths from 3/16" to 3/4"	1

## BAND-IT® Tool

Standard BAND-IT® Banding Tool used on band widths of 3/16" to 3/4". Comes with a spin handle retaining ring to keep parts intact.



**BAND-IT® Tool**

Part No	Description	Package Quantity
C00169	Standard BAND-IT® Banding Tool - For band widths of 3/16" to 3/4".	1



©2010 BAND-IT—IDEX  
ALL RIGHTS RESERVED  
B155 05/2011

[www.band-it-idex.com](http://www.band-it-idex.com)

BID.Insulation@idexcorp.com

Toll Free: 800-525-0758/303-320-4555