

Band-It BAND-FAST - Cable Cleat Alternative

PPA Coated BAND-FAST® Clamps

Item Code	Band Code	Clip Code	Width mm	Length mm	Single or Double Wrap	Max Cable OD Single Cable Config mm	Max Cable OD Trefoil Cable Config mm	Max Cable OD Quadrafoil Cable Config mm	Qty per Pack	Passed IEC61914:2015 Short Circuit Test in Trefoil up to (kA Peak)
CFAC-F1015M030-A900	AE435	AE455	15.88	300	Single	40	13	12	100	50.8kA
CFAC-F1015M040-A900	AE435	AE455	15.88	400	Single	75	28	25	100	50.8kA
CFAC-F1015M050-A900	AE435	AE455	15.88	500	Single	100	43	37	100	50.8kA
CFAC-F1015M060-A900	AE435	AE455	15.88	600	Single	130	57	50	100	50.8kA
CFAC-F1015M070-A900	AE435	AE455	15.88	700	Single	160	70	60	100	50.8kA
CFFC-F1015M030-A900	AE435	LE155	15.88	300	Double	25	10	9	100	76.3kA
CFFC-F1015M040-A900	AE435	LE155	15.88	400	Double	40	13	12	100	76.3kA
CFFC-F1015M050-A900	AE435	LE155	15.88	500	Double	55	21	18	100	76.3kA
CFFC-F1015M060-A900	AE435	LE155	15.88	600	Double	70	28	25	100	76.3kA
CFFC-F1015M070-A900	AE435	LE155	15.88	700	Double	85	35	31	100	76.3kA
CFFC-F1015M080-A900	AE435	LE155	15.88	800	Double	100	42	37	100	76.3kA
CFFC-F1015M100-A900	AE435	LE155	15.88	1000	Double	130	57	50	100	76.3kA
CFFC-F1015M120-A900	AE435	LE155	15.88	1200	Double	160	70	60	100	76.3kA

Uncoated BAND-FAST® with Ear-Lokt Buckle

Item Code	Band Code	Buckle Code	Width mm	Length mm	Single or Double Wrap	Max Cable OD Single Cable Config mm	Max Cable OD Trefoil Cable Config mm	Max Cable OD Quadrafoil Cable Config mm	Qty per Pack	Passed IEC61914:2015 Short Circuit Test in Trefoil up to (kA Peak)
CFEC-F1030M050	C405	C455	15.88	500	Double	55	21	18	100	112kA
CFEC-F1030M060	C405	C455	15.88	600	Double	70	28	25	100	112kA
CFEC-F1030M070	C405	C455	15.88	700	Double	85	35	31	100	112kA
CFEC-F1030M080	C405	C455	15.88	800	Double	100	42	37	100	112kA
CFEC-F1030M100	C405	C455	15.88	1000	Double	130	57	50	100	112kA
CFEC-F1030M120	C405	C455	15.88	1200	Double	160	70	60	100	112kA
CFEC-F1230M050	C406	C456	19.05	500	Double	55	21	18	100	120kA
CFEC-F1230M060	C406	C456	19.05	600	Double	70	28	25	100	120kA
CFEC-F1230M070	C406	C456	19.05	700	Double	85	35	31	100	120kA
CFEC-F1230M080	C406	C456	19.05	800	Double	100	42	37	100	120kA
CFEC-F1230M100	C406	C456	19.05	1000	Double	130	57	50	100	120kA
CFEC-F1230M120	C406	C456	19.05	1200	Double	160	70	60	100	120kA

PPA Coated BAND-FAST™ Clamps with clips have 0.38mm 316SS band thickness (1.2mm thick with coating) **Use C075 Tool Only**

Uncoated BAND-FAST™ Clamps with Ear-Lokt Buckles have 0.76mm 316SS band thickness **Use C001 Tool Only**

Uncoated BAND-FAST™ Clamps with Ear-Lokt Buckles should be installed with additional polymeric channel to ensure maximum results



C075 Tool

C001 Tool